

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

**Semantics Mapping Between
Different Object Hierarchies**

Inventors:

Debi Mishra

Nikhil Jain

Sushil Baid

ATTORNEY'S DOCKET NO. MS1-929US

Semantics Mapping Between Different Object Hierarchies

TECHNICAL FIELD

This invention relates generally to methods and/or devices for enhancing portability of programming language codes and compiled codes.

BACKGROUND

An object-oriented programming language (OOPL) typically defines not only the data type of a data structure, but also the types of functions that can be applied to the data structure. In essence, the data structure becomes an object that includes both data and functions. During execution of an OOPL program, access to an object's functionality occurs by calling its methods and accessing its properties, events, and/or fields.

In an OOPL environment, objects are often divided into classes wherein objects that are an instance of the same class share some common property or properties (e.g., methods and/or instance variables). Relationships between classes form a class hierarchy, also referred to herein as an object hierarchy. Through this hierarchy, objects can inherit characteristics from other classes.

In object-oriented programming, the terms "Virtual Machine" (VM) and "Runtime Engine" (RE) have recently become associated with software that executes code on a processor or a hardware platform. In the description presented herein, the term "RE" includes VM. A RE often forms part of a larger system or framework that allows a programmer to develop an application for a variety of users in a platform independent manner. For a programmer, the application

development process usually involves selecting a framework, coding in an OOPL associated with that framework, and compiling the code using framework capabilities. The resulting platform-independent, compiled code is then made available to users, usually as an executable file and typically in a binary format. Upon receipt of an executable file, a user can execute the application on a RE associated with the selected framework.

Traditional frameworks, such as the JAVATM language framework (Sun Microsystems, Inc., Palo Alto, California), were developed initially for use with a single OOPL (i.e., monolithic at the programming language level); however, a recently developed framework, .NETTM framework (Microsoft Corporation, Redmond, Washington), allows programmers to code in a variety of OOPLs. This multi-OOPL framework is centered on a single compiled “intermediate” language having a virtual object system (VOS). As a result, the object hierarchy and the nature of the compiled code differ between the JAVATM language framework and the .NETTM framework.

For the discussion presented herein, the term “bytecode” is generally associated with a first framework and the term “intermediate language code” or “IL code” is associated with a second framework, typically capable of compiling a variety of programming languages. In a typical framework, the framework RE compiles code to platform-specific or “native” machine code. This second compilation produces an executable native machine code. Throughout the following description, a distinction is drawn between the first compilation process (which compiles a programming language code to bytecode or an intermediate

1 language code) and the second compilation process (which compiles, for example,
2 a bytecode or an intermediate language code to native machine code/instructions).
3 In general, a “compiled code” (or “compiled codes”) refers to the result of the first
4 compilation process.
5

6 To enhance portability of programming languages and compiled codes,
7 there is a need for methods and/or devices that can perform the following acts: (i)
8 compile a programming language code associated with a first framework (e.g., a
9 bytecode framework) to a compiled code associated with a second framework
10 (e.g., an IL code framework); and/or (ii) convert a compiled code associated with a
11 first framework (e.g., a bytecode framework) to a compiled code associated with a
12 second framework (e.g., an IL code framework). Such methods and/or devices
13 should account for differences in object hierarchy and perform without
14 substantially compromising the original programmer’s intent.
15

16 SUMMARY

17 To enhance portability of programming languages and compiled codes,
18 methods and/or devices described herein optionally compile a programming
19 language code associated with one framework to a code associated with another
20 framework; and/or convert a code associated with one framework to a code
21 associated with another framework. The aforementioned devices and/or methods
22 include, but are not limited to, features for supporting framework differences in
23 object hierarchy, exceptions, type characteristics, reflection transparency, and
24 scoping. Such methods and/or devices optionally account for differences in object
25

1 hierarchy and perform without substantially compromising the original
2 programmer's intent.

3
4 Additional features and advantages of the invention will be made apparent
5 from the following detailed description of illustrative embodiments, which
6 proceeds with reference to the accompanying figures.

7 8 **BRIEF DESCRIPTION OF THE DRAWINGS**

9 A more complete understanding of the various methods and arrangements
10 described herein, and equivalents thereof, may be had by reference to the
11 following detailed description when taken in conjunction with the accompanying
12 drawings wherein:

13 Fig. 1 is a block diagram generally illustrating an exemplary computer
14 system on which the present invention may be implemented.

15 Fig. 2 is a block diagram illustrating two different frameworks as known to
16 one of ordinary skill in the art.

17 Fig. 3 is a block diagram illustrating two frameworks and an exemplary
18 converter for converting a bytecode to an IL code.

19 Fig. 4 is a block diagram illustrating an object hierarchy for a framework
20 using bytecode.

21 Fig. 5 is a block diagram illustrating an exemplary combined object
22 hierarchy.

23 Fig. 6 is a block diagram illustrating an exemplary combined object
24 hierarchy including an ObjectForArrays class.

1 Fig. 7 is a block diagram illustrating two frameworks and an exemplary
2 converter for converting classes.

3 Fig. 8 is a block diagram illustrating the JAVATM language framework's
4 exception hierarchy.

5 Fig. 9 is a block diagram illustrating an exemplary combined exception
6 hierarchy.

7 Fig. 10 is a block diagram illustrating an alternative exemplary combined
8 exception hierarchy.

9 Fig. 11 is a block diagram illustrating an exemplary converter including
10 features for supporting differences in object hierarchy, exceptions, type
11 characteristics, reflection transparency, and scoping.

12 **DETAILED DESCRIPTION**

13
14 Turning to the drawings, wherein like reference numerals refer to like
15 elements, various methods and converters are illustrated as being implemented in a
16 suitable computing environment. Although not required, the methods and
17 converters will be described in the general context of computer-executable
18 instructions, such as program modules, being executed by a personal computer.
19 Generally, program modules include routines, programs, objects, components, data
20 structures, etc. that perform particular tasks or implement particular abstract data
21 types. Moreover, those skilled in the art will appreciate that the methods and
22 converters may be practiced with other computer system configurations, including
23 hand-held devices, multi-processor systems, microprocessor based or
24 programmable consumer electronics, network PCs, minicomputers, mainframe
25 computers, and the like. The methods and converters may also be practiced in

1 distributed computing environments where tasks are performed by remote
2 processing devices that are linked through a communications network. In a
3 distributed computing environment, program modules may be located in both local
4 and remote memory storage devices.

5
6 Fig.1 illustrates an example of a suitable computing environment 120 on
7 which the subsequently described methods and converter arrangements may be
8 implemented.

9
10 Exemplary computing environment 120 is only one example of a suitable
11 computing environment and is not intended to suggest any limitation as to the
12 scope of use or functionality of the improved methods and arrangements described
13 herein. Neither should computing environment 120 be interpreted as having any
14 dependency or requirement relating to any one or combination of components
15 illustrated in computing environment 120.

16
17 The improved methods and arrangements herein are operational with
18 numerous other general purpose or special purpose computing system
19 environments or configurations. Examples of well known computing systems,
20 environments, and/or configurations that may be suitable include, but are not
21 limited to, personal computers, server computers, thin clients, thick clients, hand-
22 held or laptop devices, multiprocessor systems, microprocessor-based systems, set
23 top boxes, programmable consumer electronics, network PCs, minicomputers,
24 mainframe computers, distributed computing environments that include any of the
25 above systems or devices, and the like.

1
2 As shown in Fig. 1, computing environment 120 includes a general-purpose
3 computing device in the form of a computer 130. The components of computer
4 130 may include one or more processors or processing units 132, a system
5 memory 134, and a bus 136 that couples various system components including
6 system memory 134 to processor 132.

7
8 Bus 136 represents one or more of any of several types of bus structures,
9 including a memory bus or memory controller, a peripheral bus, an accelerated
10 graphics port, and a processor or local bus using any of a variety of bus
11 architectures. By way of example, and not limitation, such architectures include
12 Industry Standard Architecture (ISA) bus, Micro Channel Architecture (MCA)
13 bus, Enhanced ISA (EISA) bus, Video Electronics Standards Association (VESA)
14 local bus, and Peripheral Component Interconnects (PCI) bus also known as
15 Mezzanine bus.

16
17 Computer 130 typically includes a variety of computer readable media.
18 Such media may be any available media that is accessible by computer 130, and it
19 includes both volatile and non-volatile media, removable and non-removable
20 media.

21
22 In Fig. 1, system memory 134 includes computer readable media in the
23 form of volatile memory, such as random access memory (RAM) 140, and/or non-
24 volatile memory, such as read only memory (ROM) 138. A basic input/output
25 system (BIOS) 142, containing the basic routines that help to transfer information

1 between elements within computer 130, such as during start-up, is stored in ROM
2 138. RAM 140 typically contains data and/or program modules that are
3 immediately accessible to and/or presently being operated on by processor 132.
4

5 Computer 130 may further include other removable/non-removable,
6 volatile/non-volatile computer storage media. For example, Fig. 1 illustrates a
7 hard disk drive 144 for reading from and writing to a non-removable, non-volatile
8 magnetic media (not shown and typically called a "hard drive"), a magnetic disk
9 drive 146 for reading from and writing to a removable, non-volatile magnetic disk
10 148 (e.g., a "floppy disk"), and an optical disk drive 150 for reading from or
11 writing to a removable, non-volatile optical disk 152 such as a CD-ROM, CD-R,
12 CD-RW, DVD-ROM, DVD-RAM or other optical media. Hard disk drive 144,
13 magnetic disk drive 146 and optical disk drive 150 are each connected to bus 136
14 by one or more interfaces 154.
15

16 The drives and associated computer-readable media provide nonvolatile
17 storage of computer readable instructions, data structures, program modules, and
18 other data for computer 130. Although the exemplary environment described
19 herein employs a hard disk, a removable magnetic disk 148 and a removable
20 optical disk 152, it should be appreciated by those skilled in the art that other types
21 of computer readable media which can store data that is accessible by a computer,
22 such as magnetic cassettes, flash memory cards, digital video disks, random access
23 memories (RAMs), read only memories (ROM), and the like, may also be used in
24 the exemplary operating environment.
25

1 A number of program modules may be stored on the hard disk, magnetic
2 disk 148, optical disk 152, ROM 138, or RAM 140, including, e.g., an operating
3 system 158, one or more application programs 160, other program modules 162,
4 and program data 164.

5
6 The improved methods and arrangements described herein may be
7 implemented within operating system 158, one or more application programs 160,
8 other program modules 162, and/or program data 164.

9
10 A user may provide commands and information into computer 130 through
11 input devices such as keyboard 166 and pointing device 168 (such as a "mouse").
12 Other input devices (not shown) may include a microphone, joystick, game pad,
13 satellite dish, serial port, scanner, camera, etc. These and other input devices are
14 connected to the processing unit 132 through a user input interface 170 that is
15 coupled to bus 136, but may be connected by other interface and bus structures,
16 such as a parallel port, game port, or a universal serial bus (USB).

17
18 A monitor 172 or other type of display device is also connected to bus 136
19 via an interface, such as a video adapter 174. In addition to monitor 172, personal
20 computers typically include other peripheral output devices (not shown), such as
21 speakers and printers, which may be connected through output peripheral interface
22 175.

23
24 Logical connections shown in Fig. 1 are a local area network (LAN) 177
25 and a general wide area network (WAN) 179. Such networking environments are

1 commonplace in offices, enterprise-wide computer networks, intranets, and the
2 Internet.

3
4 When used in a LAN networking environment, computer 130 is connected
5 to LAN 177 via network interface or adapter 186. When used in a WAN
6 networking environment, the computer typically includes a modem 178 or other
7 means for establishing communications over WAN 179. Modem 178, which may
8 be internal or external, may be connected to system bus 136 via the user input
9 interface 170 or other appropriate mechanism.

10
11 Depicted in Fig. 1, is a specific implementation of a WAN via the Internet.
12 Here, computer 130 employs modem 178 to establish communications with at
13 least one remote computer 182 via the Internet 180.

14
15 In a networked environment, program modules depicted relative to
16 computer 130, or portions thereof, may be stored in a remote memory storage
17 device. Thus, e.g., as depicted in Fig. 1, remote application programs 189 may
18 reside on a memory device of remote computer 182. It will be appreciated that the
19 network connections shown and described are exemplary and other means of
20 establishing a communications link between the computers may be used.

21 22 Converters and Conversion Processes

23 To enhance portability of programming languages and compiled codes,
24 methods and converters are presented herein to perform the following acts: (i)
25 compile a programming language code associated with a first framework (e.g., a

bytecode framework) to a compiled code associated with a second framework (e.g., an IL code framework); and/or (ii) convert a compiled code associated with a first framework (e.g., a bytecode framework) to a compiled code associated with a second framework (e.g., an IL code framework). While various examples presented herein include a first framework comprising a bytecode framework and a second framework comprising an IL code framework, the exemplary converters and exemplary methods are not limited to bytecode and IL code frameworks. Further, conversion optionally includes conversions between bytecode frameworks, conversions between IL code frameworks and/or conversions to, from and/or between other types of frameworks known in the art. Additional features are discussed below that help to retain the original programmer's intent.

Fig. 2 shows a block diagram of a first framework comprising a bytecode framework 200, a second framework comprising an IL code framework 300 and a converter 400. The bytecode framework 200 includes a source code block 204 for a source code written in an OOPL, such as the JAVATM programming language (Sun Microsystems, Inc., Palo Alto, California). A compiler block 208 compiles the source code to produce a bytecode, shown in bytecode block 212. Next, a RE block 216 receives bytecode from the bytecode block 212. At run time the RE block 216 interprets and/or compiles and executes native machine code/instructions to implement applications embodied in the bytecode.

The IL code framework 300 includes a source code block 304 for a source code written in an OOPL, such as VISUAL C#TM (Microsoft Corporation, Redmond, Washington). A compiler block 308 compiles the source code to

1 produce an IL code, shown in IL code block 312. The compiler block 308
2 optionally has the capability of compiling more than one type of OOPL. The IL
3 code block 312 may also include metadata, which helps the RE manage objects.
4 Next, a RE block 316 receives IL code from the IL code block 312. At run time
5 the RE block 316 compiles and executes native machine code/instructions to
6 implement applications embodied in the IL code.

7
8 The converter 400 converts various operations and/or code between one
9 framework and another as desired and/or as required. A variety of exemplary
10 converters are described below.

11
12 Fig. 3 shows the block diagram of Fig. 2 further including an exemplary
13 converter block 400 that converts bytecode to IL code and another exemplary
14 converter block 430 that converts an OOPL code to an IL code. While the
15 description below focuses primarily on the bytecode to IL code converter block
16 400, the OOPL code to IL code converter 430 addresses similar issues.

17
18 The converter 400 accounts for a variety of issues including differences in
19 object hierarchies. As a specific example, consider the object hierarchy of the
20 OOPL-based JAVATM language framework. In the JAVATM language framework, a
21 class known as the "Object" class sits at the base of the class hierarchy, this Object
22 class appears herein as java.lang.Object. Referring to the object hierarchy 500
23 shown in Fig. 4, the java.lang.Object class 504 appears at the base of the hierarchy
24 500. The java.lang.Object class 504 defines the basic state and behavior of all
25 objects. All other classes descend either directly or indirectly from the Object

1 class 504. As shown in Fig. 4, class X1 508, class X2 512 and class X3 516 are
2 subclasses of the java.lang.Object class 504, which is a superclass of these
3 subclasses. A subclass inherits state and behavior in the form of variables and
4 methods from its superclass. Subclasses Y1 520 and Y2 524 inherit from classes
5 X1 508 and X3 516, respectively, as well as from java.lang.Object class 504.

6 7 Supporting an Object Hierarchy

8 To adequately convert bytecode of the JAVATM language framework to IL
9 code of the .NETTM framework, the converter should ensure that the object
10 hierarchy of the JAVATM language framework inherits from a class within the
11 .NETTM object hierarchy. In the .NETTM framework, the base class is the
12 System.Object class. Fig. 5 shows a combined object hierarchy 600 wherein a
13 java.lang.Object class 504 and related subclasses (508, 512, 516, 520, 524) inherit
14 from a .NETTM System.Object class 604.

15
16 The combined object hierarchy 600, as shown in Fig. 5, however, may not
17 adequately account for differences in arrays. In the JAVATM language framework,
18 arrays are objects and inherit from java.lang.Object 504 directly. Thus, assuming
19 that class X2 512 is an array creation class called java.array, this class should
20 inherit from java.lang.Object 504 and System.Object 604. However, the IL code
21 of the .NETTM framework supports creation of arrays only as instances of an array
22 class, known as System.Array 606, note that java.lang.Object 504 does not inherit
23 from System.Array 606. Thus, whenever a method call tries to treat an array as a
24 java.langObject, it would fail. For example, consider the following JAVATM
25 language code:

1 new int[2].objectMethod();

2
3 This code will fail because the object created by “new int[2]” is not an instance of
4 java.lang.Object, i.e., any attempt to call the method objectMethod() of
5 java.lang.Object will fail. Therefore, to adequately account for a JAVA™
6 language framework array, the java.array class that inherits from System.Array
7 606 should also inherit from java.lang.Object 504.

8
9 An additional aspect of the array issue involves type checking of array
10 assignments. For example, consider the following code for executing an
11 assignment:


12 Object[] obj = {new int[2], “nikhil”};

13 This code tries to assign an array to an element of java.lang.Object[]; however,
14 the array is not an instance of java.lang.Object. Strict type checking at runtime for
15 array element assignments in .NET™ framework ensures that an exception (e.g.,
16 ArrayTypeMismatchException) gets thrown at runtime.

17
18 An exemplary procedure for handling these java.array inheritance issues
19 involves the creation of a new class, referred to herein as ObjectForArrays.
20 Referring to Fig. 6, a combined object hierarchy 700 is shown including
21 ObjectForArrays 720. In this object hierarchy 700, ObjectForArrays 720 inherits
22 from java.lang.Object 708 and java.array 716 inherits through System.Array 712
23 and both java.lang.Object 708 and System.Array 712 inherit through
24 System.Object 704. In an exemplary method, the ObjectForArray class 720 is
25 used whenever an attempt is made to use an array like an object. The methods of

the ObjectForArray class 720 are static and take an extra parameter that is the object on which the java.lang.Object method call is intended. The difference though, is that this parameter is a System.Object 704 rather than a java.lang.Object 708. Hence, this object hierarchy 700 can handle arrays.

The following exemplary code illustrates aspects of the object hierarchy 700 shown in Fig. 6.



Whenever an array is treated like a `java.lang.Object`, a converter converts the code. For example, consider the following converter operation:

Code Before Compilation

```
int [ ] i = new int [2];
i.objectMethod ( );
```

Implied Code After Conversion

```
int [ ] i = new int [2];
ObjectForArrays.objectMethod(i);
```

In the instance where a `java.lang.Object` method is called on an object whose type is not known at compilation time, a converter converts the corresponding code in the following exemplary manner:

1
2
3
4

```
public void m(Object obj)
{
    obj.objectMethod( );
}
```



6
7
8
9

```
public void m(Object obj)
{
    if (obj instanceof System.Array)
        ObjectForArrays.objectMethod (obj);
    else
        obj.objectMethod( );
}
```

10
11 Referring again to Fig. 3, as described above, an exemplary converter 400
12 converts code from one framework, e.g., the JAVA™ language framework, to an
13 executable code in another framework, e.g., the .NET™ framework. The
14 converter 400 handles framework array element assignment issues by ensuring an
15 inheritance check of the object being assigned inheriting from the type of the
16 runtime array passes. For example, referring to the combined object hierarchy
17 600 of Fig. 5, whenever a need exists for java.lang.Object 504 array creation, the
18 exemplary converter 400 creates System.Object 604 arrays. In the conversion
19 process, the converter 400 does not change the signature of the field or the local
20 variable; only the actual object created gets changed.

21
22
23

```
java.lang.Object[] obj = new java.lang.Object[2];
obj[0] = new int[2];
```



25

```
java.lang.Object[] obj = new System.Object[2];
obj[0] = new int[2];
```

1
2 According to this exemplary converter 400 and conversion process, the
3 underlying `System.Object[]` behaves seamlessly like a `java.lang.Object[]`. Note
4 that the brackets “[]” represent an operator or action such as declaration of an
5 array, creation of an array, and access of array elements. In a further aspect of this
6 exemplary converter 400, whenever a user attempts to reflect upon the type of the
7 object by using `getClass()` method in `java.lang.Object` 504 on the object, the
8 `getClass` code returns the type as `java.lang.Object[]` and not `System.Object[]`.
9

10 In yet another aspect, the exemplary converter 400 handles arrays created
11 through a reflection API. In the JAVATM language framework, a reflection API
12 (e.g., available through the command “import java.lang.reflect.*”) can generally
13 be used to determine the class of an object; to get information about a class's
14 modifiers, fields, methods, constructors, and superclasses; to find out what
15 constants and method declarations belong to an interface; to create an instance of a
16 class whose name is not known until runtime; to get and set the value of an
17 object's field, even if the field name is unknown to your program until runtime; to
18 invoke a method on an object, even if the method is not known until runtime; and
19 to create a new array, whose size and component type are not known until runtime,
20 and then modify the array's components.
21

22 According to the exemplary converter 400, when a code calls for creation
23 of a `java.lang.Object[]` array using the reflection API (e.g., using
24 `Array.newInstance`), the converter 400 creates a corresponding `System.Object[]`.
25

1 The exemplary converter 400 further accounts for verification issues upon
2 assignment of a System.Object[] to a field of type java.lang.Object [].

3
4 Another aspect of the exemplary converter 400 handles code containing
5 “instanceof” checks on an array. An object is considered to be an instance of a
6 class if that object directly or indirectly descends from that class. In the JAVATM
7 language framework, “instanceof” determines whether a first operand is an
8 instance of a second operand wherein, for example, the first operand is the name
9 of an object and the second operand is the name of a class. To ensure that
10 “instanceof” calls on arrays succeed for java.lang.Object, java.lang.Cloneable and
11 java.io.Serializable, the exemplary converter 400 includes the following operation
12 (shown for java.lang.Cloneable):

13 Boolean b = obj instanceof java.lang.Cloneable;



16 Boolean b = obj instanceof java.lang.Cloneable ||
17 obj instanceof System.Array;

18 Regarding the clone method, in the JAVATM language framework,
19 implementation of this method checks to see if the object on which clone was
20 invoked implements the Cloneable interface, and throws a
21 CloneNotSupportedException if it does not. In particular, note that Object itself
22 does not implement Cloneable, so subclasses of Object that do not explicitly
23 implement the interface are not cloneable. Thus, the exemplary converter 400
24 accounts for this characteristic of the JAVATM language framework. In a similar
25 vein, in the JAVATM language framework, an object is serializable only if its class

implements the Serializable interface. Thus, code that seeks to serialize instances of a class requires that the class implement the Serializable interface. Again, the exemplary converter 400 accounts for this characteristic of the JAVATM language framework.

Boolean b = obj instanceof java.lang.Serializable;



Boolean b = obj instanceof java.lang.Serializable ||
obj instanceof System.Array;

JAVATM language framework like most OOPs has a set of class libraries that are used by programmers as a foundation to build applications. Supporting compilation and execution of such applications optionally requires implementation of these class libraries on the .NETTM framework. Fig. 7 shows a block diagram illustrating two frameworks 200, 300 and an exemplary converter 460 for converting classes 444. Accordingly, the exemplary converter 460 optionally allows for implementation of reflection in a first framework 200 (e.g., JAVATM language framework) on top of reflection in a second framework 300 (e.g., .NETTM framework). Such an exemplary converter 460 converts classes written in source code (e.g., an OOP code) and/or classes that exist in a compiled code (e.g., bytecode or other compiled code) (see, e.g., Figs. 2 and 3, the converter 400 and the converter 430). While Fig. 7 refers to bytecode framework classes 444, which are available to the bytecode framework RE 216 and/or the compiler for the bytecode framework 208, the classes are optionally classes associated with yet another framework. A class converted by such a converter and associated with a

1 second framework is optionally referred to herein as a first framework class, a
2 converted class, and/or a new class.

3
4 In the .NETTM framework, System.Type is the root object of .NETTM
5 framework reflection mechanism, wherein a type object describes a class. Thus,
6 for example, a reflection to get information about a class's modifiers, fields,
7 methods, constructors, and superclasses uses the underlying System.Type object.
8 For arrays, the type object for arrays is the type object for the .NETTM framework
9 arrays, which are an instance of System.Array. The class library implementation
10 accounts for this difference because reflection on a .NETTM framework array gives
11 different results than an ordinary reflection on a JAVATM framework array. An
12 exemplary method for class library implementation handles this particular issue in
13 a way that maintains the original programmer's intent.

14
15 In yet another aspect, an exemplary converter optionally accounts for
16 verification issues related to difference between frameworks. For example, a
17 verification issue arises upon assignment of an array to fields of types
18 java.lang.Object. Similarly, a verification issue arises for creation of
19 System.Object arrays in place of java.lang.Object arrays when assigning a field of
20 type java.lang.Object ("JLO") to one of the System.Object ("SO") arrays. The
21 exemplary converter 400 handles these issues by isolating them into a file having
22 static methods. For example, a file named VerifierFix has static methods by the
23 name getJLOFromSO that take SO or SO[] . . . [] as a parameter and return JLO
24 or JLO[] . . . [] correspondingly. This process results in isolation of all
25 verification issues into one class VerifierFix and hence all other binaries generated

1 by the compiler would not hit any of these verification issues. The following
2 operation demonstrates a process for handling verification issues.

```
3 java.lang.Object obj = new obj[2];  
4 java.lang.Object[ ] obj1 = new java.lang.Object[2]
```



```
6 java.lang.Object obj =  
7     VerifierFixgetJLOFromSO(new int[2]);  
8 java.lang.Object[ ] obj1 =  
9     VerifierFix.getJLOFromSO(new System.Object[2]);
```

10 Note that the above call to VerifierFix.getJLOFromSO calls different
11 overloaded methods in the two cases shown above. The first one takes an SO and
12 returns a JLO and the second one takes a SO[] and returns a JLO[].

13
14 As already mentioned, a reflection can also be used to set the value of an
15 object's field. Such reflection operations may differ from one framework to
16 another. Thus, the exemplary converter 400 optionally accounts for such
17 differences. For example, when code from a JAVATM language framework
18 executes on a .NETTM runtime, any attempt to set an array to a field type of
19 java.lang.Object will fail. The failure is due to the fact that arrays in the .NETTM
20 framework do not normally inherit from java.lang.Object. Consequently, the
21 .NETTM reflection API causes an exception. As a remedy, the exemplary converter
22 400 emits a private method that takes a System.Object as an argument and within
23 the method assigns this argument to the field. Thus, when a reflection call to
24 assign a value to such a field appears, the converter 400 provides for the
25 aforementioned private method. The framework invokes the private method using

1 reflection and hence bypasses the reflection check for the type of value to be
2 assigned.

3
4 At the code level, the converter's remedy optionally appears as follows:

5
6

```
class A  
{  
    java.lang.Object f;  
    java.lang.Object[ ] f1;  
}
```



11
12
13
14
15
16
17
18
19
20
21
22
23
24
25

```
class A  
{  
    java.lang.Object f;  
    java.lang.Object[ ] f1;  
    private $setf (System.Object value) {  
        f = VerifierFix.getJLOFromSO(value);  
    }  
    private $setf1 (System.Object[ ] value) {  
        f1 = VerifierFix.getJLOFromSO(value);  
    }  
}
```

17 This exemplary converter code averts the throwing of an exception by a
18 reflection API by calling the \$setf method and assigning the value, which could be
19 an array, to the field f. Note that this remedy does not impact normal use of
20 arrays, like array assignments.

21
22 In essence, the exemplary converter introduces an instanceof check when
23 arrays are used as java.lang.Object by calling a method in java.lang.Object class
24 on this array object. Further, all calls to methods of java.lang.Object where the
25 underlying object is not an array result in a method call and an instanceof check.

1 Overall, the remedy for each verification issue requires a method call. The slight
2 increase in overhead however does not detract from the goal of successfully
3 converting code from one framework to another while retaining the programmer's
4 original intent.

6 Supporting Framework Exceptions

7 The exemplary converter 400, described herein (see, e.g., "Supporting a
8 Framework Object Hierarchy"), optionally includes features that support
9 exceptions from one framework on another framework. For example, consider the
10 JAVATM language exception hierarchy 800 shown in Fig. 8. JAVATM language
11 public class Object 804 sits at the base of the JAVATM language framework's
12 hierarchy 800 such that every class has Object 804 as a superclass. As described
13 previously, all objects, including arrays, inherit the methods of the
14 java.lang.Object class 804.

15
16 In the exception hierarchy 800, the class java.lang.Throwable 808 sits
17 below java.lang.Object 804. The Throwable class 808 is the superclass of all
18 errors and exceptions in the JAVATM language framework. Only objects that are
19 instances of this class (or of one of its subclasses) are thrown by the JAVATM
20 language RE or can be thrown by a "throw" statement. Similarly, only this class
21 or one of its subclasses can be the argument type in a catch clause. In the JAVATM
22 language framework, the Throwable class 808 also contains a snapshot of the
23 execution stack of its thread at the time it was created.

1 As mentioned, the Throwable class 808 is the superclass of all errors and
2 exceptions in the JAVATM language framework. Thus, the classes
3 java.lang.Exception 812 and java.lang.Error 816 sit below java.lang.Throwable
4 808 in the hierarchy 800. In general, the class java.lang.Exception 812 and its
5 subclasses, java.lang.RuntimeException 820 (unchecked exceptions) and Java
6 Checked Exceptions 824, are forms of Throwable 808 that indicate conditions that
7 a reasonable application might want to catch. Also shown in Fig. 8 is a subclass of
8 java.lang.RuntimeException 820 entitled "Other Java Runtime Exceptions" 828,
9 which simply recognizes the possibility of other runtime exceptions. The
10 java.lang.Error 816 class is a subclass of Throwable 808. The Error class 816
11 indicates serious problems (e.g., abnormal conditions) that a reasonable
12 application should not try to catch.

13
14 A list of exceptions and/or errors thrown by the JAVATM language RE
15 appears below.

16 java.lang.ArithmeticException

17 java.lang.ArrayIndexOutOfBoundsException

18 java.lang.ArrayStoreException

19 java.lang.ClassCastException

20 java.lang.Error

21 java.lang.Exception

22 java.lang.IllegalAccessError

23 java.lang.IllegalArgumentException

24 java.lang.IllegalMonitorStateException

25 java.lang.IllegalThreadStateException

java.lang.IncompatibleClassChangeError
 java.lang.IndexOutOfBoundsException
 java.lang.InternalError
 java.lang.InterruptedOperationException
 java.lang.LinkageError
 java.lang.NoClassDefFoundError
 java.lang.NoSuchFieldError
 java.lang.NoSuchMethodError
 java.lang.NullPointerException
 java.lang.NumberFormatException
 java.lang.OutOfMemoryError
 java.lang.RuntimeException
 java.lang.SecurityException
 java.lang.StackOverflowError
 java.lang.ThreadDeath
 java.lang.Throwable
 java.lang.UnsatisfiedLinkError
 java.lang.VerifyError
 java.lang.VirtualMachineError

Exception handling in the .NET™ framework involves definition of exception blocks. At the IL level, exception block definition occurs predominantly through use of either catch types or filter blocks. For example, catch type exception handling may include a BeginExceptionBlock() followed by emission of some IL code; a BeginCatchBlock(ExceptionType) followed by emission of

1 some IL code; and an EndExceptionBlock. Filter block definition handling may
2 include a BeginExceptionBlock() followed by emission of some IL code; a
3 BeginFilterBlock() followed by emission of some IL code; a
4 BeginCatchBlock(null) followed by emission of some IL code; and an
5 EndExceptionBlock.

6
7 When defining catch type exception blocks through the .NET™
8 Framework's Reflection APIs, ExceptionType must be an instance of the .NET™
9 framework's System.Exception class; however, at the IL level there is no such
10 limitation. Thus, whenever an exception gets thrown, control goes to the entered
11 catch block if the exception thrown is an instance of ExceptionType.

12
13 In contrast, when an exception is thrown according to a filter block
14 exception block, control goes to the .NET™ framework's ExceptionFilterBlock
15 class. According to this scenario, the thrown exception is placed on top of the
16 stack wherein the filter block is used to indicate, for example, a 0 or 1. If the filter
17 block indicates 1, when the filter block ends, the .NET™ framework enters a catch
18 block. If the filter block indicates 0, then the exception goes uncaught by this
19 particular exception block. Hence, in this manner, the filter block filters
20 exceptions by either allowing them to go uncaught or directing them to a catch
21 block.

22
23 To handle JAVA™ language framework exceptions on the .NET™
24 framework, a converter should account for several issues. For example, in the
25 JAVA™ language framework, Errors (instance of java.lang.Error 816) and runtime

1 exceptions (instance of java.lang.RuntimeException 820) can be thrown by the
2 JAVA™ language RE. When a program executes on the .NET™ RE, the
3 exceptions thrown by the runtime are different from those thrown by JAVA™
4 language RE. The following code illustrates such an instance wherein the .NET™
5 framework would fail to catch the exception thrown.

```
6      try {  
7          int k = 0;  
8          int j = 5/k;    //causes a runtime exception  
9      } catch (Exception e) {  
10      }  
11
```

10 Without an exception conversion (e.g., code conversion or mapping), the
11 exception thrown for the above code will not be an instance of java.lang.Exception
12 812 and hence it will not be caught. Further, a complete one-to-one mapping does
13 not exist for many frameworks. For example, a complete one-to-one mapping
14 does not exist between JAVA™ language exceptions and .NET™ exceptions.
15 Thus, an exemplary converter for handling exceptions accounts for differences in
16 exception class hierarchy and for the lack of a complete one-to-one mapping.

17
18 An exemplary converter converts and/or maps JAVA™ language
19 framework exceptions to existing and/or new .NET™ framework exceptions.
20 According to this exemplary converter, catch types are used to catch various
21 JAVA™ language exceptions. For checked exceptions (exceptions not normally
22 thrown by either the JAVA™ language or .NET™ RE), the catch type approach
23 suffices; however, for runtime exceptions and errors the exemplary converter
24 implements filter blocks.
25

1 Given a JAVA™ language framework exception throwable by the JAVA™
2 language RE, the exemplary converter needs to find a corresponding .NET™
3 framework exception throwable by the .NET™ RE. The exemplary converter
4 should also catch the JAVA™ language exception because, like any checked
5 exception, the associated JAVA™ language code could throw the exception
6 explicitly.

7
8 To address this particular issue, the exemplary converter implements filter
9 blocks. During a conversion process, the converter emits IL code for a filter block
10 designed to catch a targeted exception or exceptions. The following code
11 illustrates the conversion process:

```
12  
13 try {  
14     Try code{ }  
15 } catch(MyException e) {  
16     catch code{ }  
17 }
```



```
18 try {  
19     try code { }  
20 } filter(System.Object exc) {  
21     filter code { }  
22 } catch {  
23     Thread.___getExceptionObject( );  
24     Catch code{ }  
25 }
```

23 Note that this particular code segment represents code implied by the IL as
24 converted from JAVA™ language code.

1 The exemplary converter may also implement mapping procedures such as
2 a static mapping from a .NET™ framework exception to a JAVA™ language
3 framework exception, which is used via a method in class java.lang.Throwable.
4 The following code illustrates part of the process:

```
5 public static Throwable __mapCorException (System.Exception exc)
```

6
7 Assuming a class “A” that is a JAVA™ language framework exception can
8 be thrown by the RE, the class library implementation for this class implements
9 the following method:

```
10 public static int __exceptFilter(System.Object o) {  
11     Throwable t = null;  
12     if (o instanceof A) {  
13         t = (A)o;  
14     }else if (o instanceof System.Exception ) {  
15         System.Exception e = (System.Exception)o;  
16         t = Throwable.__mapCorException(e);  
17         if (t != null) {  
18             t.__updateException(e);  
19         }  
20     }  
21     if (t != null) {  
22         Thread.__setExceptionObject(t);  
23         return 1;  
24     }else  
25         return 0;  
26 }
```

20 Converter 400 during the conversion process emits the filter code that calls
21 this method, passing the exception object as a parameter. Thus, via this process,
22 the converter implemented filter block allows the .NET™ framework to catch both
23 the .NET exception and the JAVA™ language exception.

1 In the above code, the method “__setExceptionObject()” is a static method
2 in class java.lang.Thread (a subclass of java.lang.Object) that stores an exception
3 object for loading back on top of the stack upon entry of a catch block. Hence,
4 while emitting IL for a catch block, a preliminary procedure emits IL having the
5 following implied code:

6 Thread.__getExceptionObject();

7
8 Through this process, the exception object gets loaded on top of the stack, as
9 expected by the code of the catch block.

10
11 Following code represents the net implied conversion:

12 try {
13 try code{}
14 } catch(MyException e) {
15 catch code{}
16 }



17 try {
18 try code{}
19 } filter(System.Object exc) {
20 Exception.__exceptFilter(exc);
21 } catch {
22 Thread.__getExceptionObject();
23 }

24 The conversion process described above assumes that a .NET™ exception
25 corresponds to only one JAVA™ language exception. In instances where one
.NET™ exception corresponds to more than one JAVA™ language exception, the
exemplary converter implements the following procedure. Consider a case where

1 a .NET™ exception “C” maps to JAVA™ language exceptions “A” and “B”. To
2 handle case, the JAVA™ language exception to which the .NET™ exception
3 corresponds, most of the time, (e.g., “A”) is marked as corresponding to .NET™
4 exception “C” in a static table and in a “__exceptFilter()” for JAVA™ language
5 exception “B”, apart from using “__mapCorException()”, the procedure explicitly
6 checks whether the exception thrown is “C”, if so, then the procedure returns or
7 indicates 1.

8
9 In the case of a thrown .NET™ exception that is an instance of
10 System.SystemException and does not have a JAVA™ language exception
11 equivalent, the thrown .NET™ exception is mapped to a
12 java.lang.RuntimeException. Otherwise the procedure maps the .NET™
13 exception to null. To the filter block, null indicates avoidance of catch block
14 exception handling, i.e., that the process should not or will not enter a catch block.

15
16 The exemplary converter for handling exceptions further allows uncaught
17 exceptions thrown by the .NET™ framework RE to optionally appear to a user, for
18 example, as a corresponding JAVA™ language framework exception.

19
20 In the JAVA™ language framework, a thread group represents a set of
21 threads. In addition, a thread group (ThreadGroup) can also include other thread
22 groups. The thread groups form a tree in which every thread group except the
23 initial thread group has a parent. In any particular thread, the JAVA™ language
24 RE calls the method ThreadGroup.uncaughtException when a thread in this thread
25 group stops because of an uncaught exception. The uncaughtException method of

1 ThreadGroup does the following: If this thread group has a parent thread group,
2 the uncaughtException method of that parent is called with the same two
3 arguments (Thread "t" and Throwable "e"). Otherwise, this method determines if
4 the Throwable argument is an instance of ThreadDeath. If so, nothing special is
5 done. Otherwise, the Throwable's printStackTrace method is called to print a stack
6 back trace to the standard error stream. In the JAVATM language framework,
7 applications can also override this method in subclasses of ThreadGroup to
8 provide alternative handling of uncaught exceptions.

9
10 In the .NETTM framework, the exemplary converter optionally instructs for
11 the use of AppDomain.AddOnUnhandledException() to register the
12 UnhandledExceptionHandler for an AppDomain wherein the handler is
13 optionally created with a delegate method, e.g.,
14 "java.lang.Thread.__unCaughtException". Accordingly,
15 AddOnUnhandledException calls on the current thread whenever there is an
16 uncaught exception wherein Thread.__unCaughtException() then calls
17 ThreadGroup.uncaughtException(). In general, for the .NETTM framework, all
18 user defined exceptions (even if they are runtime exceptions) are treated like
19 checked exceptions because they are not thrown by the .NETTM RE.

20
21 The aforementioned exemplary converter allows a code converted from the
22 JAVATM language framework to the .NETTM framework to handle exceptions
23 essentially as the original programmer intended. To achieve this goal, the
24 exemplary converter approximates the JAVATM language code as .NETTM IL code;
25 exposes three normally unspecified public methods

1 (Thread.__setExceptionObject(), Thread.__getExceptionObject() and
2 Throwable.__mapCorException()); and incurs an overhead for execution of filter
3 blocks when an exception gets thrown. However, in this exemplary converter, a
4 few issues may exist. For example, through use of such a converter, the .NET™
5 framework may not catch a JAVA™ language framework exception by catching
6 System.Exception (base class of all .NET™ exceptions) and the converter may not
7 accurately map the System.StackOverflowException. The former issue impacts
8 the ability of other .NET™ “compatible” languages (e.g., VISUAL C#™ and
9 VISUAL BASIC® execute without conversion) to consume JAVA™ language
10 classes and catch JAVA™ language exceptions while the latter issue stems from a
11 lack of stack space, i.e., when an attempt is made to map the exception thrown
12 because of lack of stack space, the check cannot be performed and
13 System.StackOverflowException gets thrown again. Of course, an exemplary
14 converter and/or method of conversion having additional features may resolve
15 such issues.

16
17 The following structures and procedures allow the exemplary converter to
18 overcome the aforementioned System.Exception issue. To catch a JAVA™
19 language exception from code written in a .NET™ language, the JAVA™
20 language exceptions must inherit from System.Exception. But
21 java.lang.Throwable (referred as JLT) inherits from JLO in the JAVA™ language
22 framework to allow JLO methods to be called on JAVA™ language exception
23 objects. Without adequate conversion, such a call would fail if JLT does not
24 inherit from JLO. Thus, an exemplary converter implements the hierarchy 900
25 shown in Fig. 9.

1
2 Referring to Fig. 9, a JavaExceptionBase ("JEB") abstract class 916
3 operates as the base class of all JAVATM language framework exceptions and
4 inherits from the .NETTM framework System.Exception class 912. According to
5 this hierarchy 900, JavaExceptionBase 916 implements all JLO methods for
6 exception objects.

7
8 In the combined exception hierarchy 900, JLT 918 does not inherit from
9 JLO 908, instead, the exemplary converter calls for special handling in the .NETTM
10 framework compiler to allow assignments where a type that derives from JEB 916
11 is treated as assignable to type JLO. According to this exemplary converter, all
12 method calls to JLO methods on JAVATM language exception objects now get
13 resolved to corresponding methods in JEB and a stack trace shows JEB in place of
14 JLO. This conversion process also allows for use of JAVATM language reflection
15 APIs to see what public methods and fields are accessible to a JAVATM exception
16 object. As a matter of convenience, JAVATM language reflection APIs
17 implemented on top of .NETTM framework should hide all public
18 System.Exception methods and fields (apart from System.Object methods and
19 fields) and reflection on JLT type for the superclass should return JLO and not
20 JEB.

21
22 Regarding instanceof checks, a check on an object being an instance of JLO
23 should return "true" even if the object is a JAVATM language exception type. The
24 exception handling procedures implemented by the exemplary converter handles
25 this particular issue in a manner similar to that for arrays (described above).

1 Accordingly, the converter generates the following converted code (e.g., from
2 source code to implied code in IL):

3 `Boolean b = obj instanceof java.lang.Object;`
4



8 `Boolean b = obj instanceof java.lang.Object ||`
9 `obj instanceof java.lang.JavaExceptionBase;`
10

11 The exemplary converter also optionally accounts for verification issues
12 when, for example, a JAVATM language exception type is assigned to a JLO.
13 Again, in a manner similar to that for arrays, the converter performs the following
14 conversion:

15 `java.lang.Object obj = new Throwable();`
16



26 `Java.lang.Object obj =`
27 `VerifierFix.getJLOFromSO(new Throwable());`

28 This particular process results in a method call for each verification issue
29 and an additional overhead for instanceof checks involving instanceof JLO. In
30 general, the exemplary converter for handling exceptions catches JAVATM
31 language framework exceptions as can any other .NET language compiler
32 however, the implication of catching a JAVATM language RE exception differs
33 slightly. For example, if JAVATM language RE exception "A" maps to .NETTM
34 exception "B", then catching "A" in converted JAVATM language code using the
35 converter 400 results in catching both "A" and "B" whereas catching "A" in other
36 .NET languages results in catching "A".

1
2 An alternative converter for handling exceptions uses a combined object
3 hierarchy such as the hierarchy 1000 shown in Fig. 10. The use of this particular
4 hierarchy 1000 alleviates the need for special handling in the .NET™ framework
5 compiler because JLT 1016 inherits from JLO 1008. However, this exemplary
6 converter may require additional features to catch JAVA™ language exceptions in
7 code written in other languages (e.g., VISUAL C#™ and VISUAL BASIC®).

8
9 Converters for handling exceptions that include mapping between .NET™
10 framework exceptions and JAVA™ language framework exceptions optionally use
11 the mapping table presented below.
12
13
14
15
16
17
18
19
20
21
22
23
24
25

Mapping Table

.NET™ Frameworks Exception	JAVA™ Language Exception
System.ArithmeticException	ArithmeticException
System.DivideByZeroException	ArithmeticException
System.OverflowException	ArithmeticException
System.IndexOutOfRangeException	ArrayIndexOutOfBoundsException
System.ArrayTypeMismatchException	ArrayStoreException
System.InvalidCastException	ClassCastException
System.MissingFieldException	NoSuchFieldError
System.Reflection.AmbiguousMatchException	NoSuchMethodError
System.MissingMethodException	NoSuchMethodError
System.MissingMemberException	IncompatibleClassChangeError
System.AccessException	IllegalAccessError
System.FieldAccessException	IllegalAccessError
System.MethodAccessException	IllegalAccessError
System.ArgumentException	IllegalArgumentException
System.ArgumentNullException	IllegalArgumentException
System.ArgumentOutOfRangeException	IllegalArgumentException
System.RankException	IllegalArgumentException
System.Threading.SynchronizationLockException	IllegalMonitorStateException
System.Threading.ThreadStateException	IllegalThreadStateException
System.NotSupportedException	InternalError
System.Threading.ThreadInterruptedException	InterruptedException
System.EntryPointNotFoundException	UnsatisfiedLinkError
System.TypeLoadException	NoClassDefFoundError
System.NullReferenceException	NullPointerException
System.FormatException	NumberFormatException
System.OutOfMemoryException	OutOfMemoryError
System.Security.SecurityException	SecurityException
System.StackOverflowException	StackOverflowError
System.Threading.ThreadStopException	<i>Depends upon execution time.</i>
System.Security.VerifierException	VerifyError
System.ExecutionEngineException	VirtualMachineError
System.SystemException	RuntimeException

Supporting Type Characteristics


Differences in type characteristics may exist between frameworks. For example, the JAVA™ language process for type casting from one primitive type to another differs from that of the .NET™ framework. The JAVA™ language

framework normally includes the types “integers” (byte, short, int and long); “real numbers” (float and double); and “other primitive types” (char and Boolean). In particular, differences exist between JAVA™ language and .NET™ frameworks in the following four cases: (i) converting a double to a long; (ii) converting a double to an int; (iii) converting a float to a long; and (iv) converting a float to an int.

In casting between real and integer, if the value of a double/float is more/less than the maximum/minimum value of a long/int, type casting in the .NET™ framework returns a “0” while type casting in the JAVA™ language framework returns the maximum/minimum value. In addition, if the original value was undefined (e.g., Not-a-Number – “NaN”), the JAVA™ language framework returns “0” while the .NET™ framework exhibits a different behavior.

An exemplary converter for handling type characteristics includes a process wherein that performs the following conversion:

```
double d = 2.0;
int i = (double)d;
```



```
double d = 2.0;
int i = Double.__convInt(d);
```

A static and public method “Double.__convInt()” converts the aforementioned boundary cases and returns the JAVA™ language framework’s expected value. In addition to this method, the exemplary converter also implements the following methods: “public static long Double.__convInt(double d)”; “public static int Float.__convInt(float f)”; and “public static long Float.__convLong(float f)”. The method Double.__convLong comprises, for example, the following code:

```

1  Public static long __convLong(double d)
2  {
3      if (d != d) // check for NAN.
4          return 0;
5      if (d >= Long.MAX_VALUE)
6          return Long.MAX_VALUE;
7      if (d <= Long.MIN_VALUE)
8          return Long.MIN_VALUE;
9      return (long)d;
10 }

```

Thus, according to this exemplary converter for handling type characteristics, four unspecified public methods take the place of IL code instructions. The overhead does not cause any significant impact because it would exist even if the .NETTM framework returned the JAVATM language framework expected value.

Supporting Reflection Transparency

An exemplary converter optionally allows for “reflection transparency” such that reflection methods are not seen in a call stack or stack trace. In the .NETTM framework, an execution stack keeps track of all the methods that are in execution at a given instant. A trace of the method calls is known as a call stack or stack trace wherein the most recent method call appears first.

In the JAVATM language framework, some reflection methods are transparent. In some transparent methods control goes over to a user code wherein, once under user code control, a user may reflect upon the call stack. These methods include: java.lang.Class.newInstance(), which creates a new instance of a class; java.lang.reflect.Constructor.newInstance(), which creates and

1 initializes a new instance of the constructor's declaring class with specified
 2 initialization parameters; and java.lang.reflect.Method.invoke(), which invokes
 3 the underlying method represented by the Method object, on the specified object
 4 with the specified parameters. To preserve functional characteristics of the
 5 JAVA™ language framework, upon conversion of JAVA™ language code to
 6 another framework, calls to these methods should not appear in a call stack.

7
 8 In the .NET™ framework, the “StackTrace” class provides reflection
 9 capabilities for examining a call stack. However, without adequate conversion,
 10 “transparent” methods in a JAVA™ language code will normally appear in the
 11 .NET™ call stack. For example, consider the following code and corresponding
 12 stacks (e.g., resulting from reflection upon the call stack within the method that is
 13 invoked):

```
public void meth1(Method method, Object[ ] params) {
    int i = Method.invoke(params);
}
```

16 An expected JAVA™ language framework-like stack would appear as follows:

InvokeMethod
meth1
The callers of meth1

21 In contrast, a .NET™ framework stack would appear as follows:

InvokeMethod
Method.invoke
meth1
The callers of meth1

1 Note that for the expected JAVATM language framework-like stack, the code call to
2 Method.invoke is transparent whereas it appears in the .NETTM framework stack.

3
4 To account for such differences, an exemplary conversion method including
5 class library implementation for handling reflection transparency checks for
6 particular methods and renders them transparent before returning the stack. In yet
7 another exemplary method, a converter introduces code that performs checks
8 and/or deletions of stack entries. For example, an exemplary converter may
9 introduce code that deletes “transparent” entries before returning a stack trace. In
10 general, as discussed throughout, a converter and/or a conversion process may
11 convert code, delete code and/or add code.

12 13 Supporting Scope

14 An exemplary converter handles scope or visibility differences between
15 frameworks. In a given framework, “scoping” normally refer to setting variable or
16 method visibility, for example, within an order of increasing visibility, e.g., local,
17 private, package, protected, and public. In the JAVATM language framework, class
18 variables have four possible levels of visibility: private, default (also known as
19 “package”), protected, and public.

20
21 A programmer typically uses scoping when a source file gets too large. For
22 example, a programmer can split a single file into individual files and then declare
23 the individual files as belonging to a package wherein the individual files share
24 variables and essentially behave as a single source file. However, in the JAVATM
25 language framework, a programmer cannot explicitly declare default or "package"

1 accessibility for variables and/or methods. At the default level, class members
2 within a package can see the “default” variable, but classes outside the package
3 that inherit from that class cannot. The JAVA™ language framework’s protected
4 accessibility attribute offers slightly more visibility. A protected variable or
5 method is visible to inheriting classes, even not part of the same package. This is
6 the only difference between the JAVA™ language framework’s protected scope
7 and default (package) scope declarations.

8
9 The .NET™ framework has scoping similarities and differences when
10 compared to the JAVA™ language framework. Public and private declarations
11 behave similarly in both JAVA™ language and .NET™ frameworks; however,
12 package and protected do not. In the JAVA™ language framework, package
13 (default) scope allows access within the same package. A package is the equivalent
14 of namespace in the .NET™ framework. Protected allows access within the same
15 family or the same package. Both protected and package scope have no direct
16 equivalent in the .NET™ framework.

17
18 To account for differences between frameworks, an exemplary converter
19 includes a process that marks package and protected as public and sets a custom
20 attribute to mark the original JAVA™ language code’s scope. According to this
21 converter, the .NET™ compiler validates the code using these attributes for
22 validations against persisted classes. In addition, JAVA™ language reflection
23 APIs also validate using these custom attributes and do not allow illegal access.
24 However, a programmer should note that use of this converter results in package
25

1 and protected scoped members being potentially exposed as public to other
2 languages or some other compiler.

3
4 In an alternative converter for handling scoping, the converter marks
5 package scope in JAVATM language as Assembly in the .NETTM framework and
6 protected scope in JAVATM language as FamilyOrAssembly in .NETTM framework.
7 Custom attributes are set in this case also and the compiler validates against these
8 attributes rather than the visibility attributes set in metadata. However, according
9 to this converter, if a package were split across assemblies, the access of a
10 package-scoped member across assemblies would fail at runtime because the
11 members are marked as assembly scoped.

12
13 Yet another converter for handling scoping combines the two
14 aforementioned exemplary converters. For example, the first described converter
15 for handling scoping is set as a default option with availability of the second
16 described converter for handling scoping as an extra option (e.g., /ss or
17 /seurescoping). Sources built using the first converter or the second converter
18 can be mixed without any problem. Thus, the user may choose whether to expose
19 protected/package scoped members as public or the user may choose the “/ss”
20 option to do more secure scoping but to prevent possible runtime failures, all
21 classes belong to a package are optionally compiled into a single assembly.

Supporting More Than One Difference

The aforementioned converters for converting code from one framework to code for another framework include features for supporting differences in object hierarchy, exceptions, type characteristics, reflection transparency, and/or scoping.

Fig. 11 shows a block diagram of the exemplary converter 400 (see, e.g., Figs. 2 and 3) that optionally includes features for supporting differences in at least one of the following: object hierarchy 402, exceptions 404, type characteristics 406, reflection transparency 408, and scoping 410. A block labeled “other” 412 also appears within the converter block 400 to account for other differences. These individual blocks represent converter features and/or conversion processes as described herein and equivalents thereof. In one exemplary converter, a user and/or a processor select features as needed or as desired. For example, a user may select only the object hierarchy feature 402 of converter 400 or alternatively use a converter that only has a feature for supporting object hierarchy differences.

In essence, for a given application, some features may have greater importance than others. In particular, if a JAVATM language code uses arrays and the user seeks to convert the code for use on the .NETTM framework, then the converter should have at least the array handling capability of the object hierarchy feature 402. Further, if debugging is important, then a user may select the exceptions feature 404.

Conversion Paths

To enhance portability of programming languages and processed codes, various exemplary converters optionally perform the following acts: (i) compile a programming language code associated with a first framework (e.g., a bytecode framework) to a compiled code associated with a second framework (e.g., an IL code framework); and/or (ii) convert a compiled code associated with a first framework (e.g., a bytecode framework) to a compiled code associated with a second framework (e.g., an IL code framework). The associated conversion methods and/or converters typically account for differences in object hierarchy and perform without substantially compromising the original programmer's intent.

Referring again to Fig. 3, two exemplary converter blocks 400, 430 optionally perform aforementioned acts. In Fig. 3, converter block 430 compiles a programming language code associated with a bytecode 204 to an IL code 312 (e.g., JAVATM programming language to MSIL) and converter block 400 converts a bytecode 212 to an IL code 312 (e.g., JAVATM language bytecode to MSIL). The foregoing description of converters for converting a compiled code associated with a first framework (e.g., bytecode framework) to a compiled code associated with a second framework (e.g., an IL code framework) applies to converters for compiling a programming language code associated with a first framework (e.g., a bytecode framework) to a compiled code associated with a second framework (e.g., an IL code framework). In particular, the converters optionally include features for supporting differences in object hierarchy, exceptions, type characteristics, reflection transparency, and/or scoping. Thus, the features shown

1 in Fig. 11 for the converter block 400 apply to converter block 430 shown in Fig. 3
2 and optionally to the converter block 460 shown in Fig. 7.
3

4 While various exemplary converters and methods described herein apply to
5 converting from a JAVATM language framework to a .NETTM framework,
6 conversions from a .NETTM framework to a JAVATM language framework are also
7 within the scope of converters and methods presented herein as well as
8 conversions to, from and/or between other frameworks known in the art.
9

10 Thus, although some exemplary methods and converters have been
11 illustrated in the accompanying Drawings and described in the foregoing Detailed
12 Description, it will be understood that the methods and converters are not limited
13 to the exemplary embodiments disclosed, but are capable of numerous
14 rearrangements, modifications and substitutions without departing from the spirit
15 set forth and defined by the following claims.
16
17
18
19
20
21
22
23
24
25